



Journal of Environmental Sciences 20(2008) 704-709

JOURNAL OF ENVIRONMENTAL SCIENCES ISSN 1001-0742 CN 11-2629/X www.jesc.ac.cn

Adsorption behavior of Azo Dye C. I. Acid Red 14 in aqueous solution on surface soils

QU Baocheng, ZHOU Jiti, XIANG Xuemin*, ZHENG Chunli, ZHAO Hongxia, ZHOU Xiaobai

School of Environmental and Biological Science and Technology, Dalian University of Technology, Dalian 116024, China. E-mail: qbch0686@yahoo.com.cn

Received 1 August 2007; revised 5 September 2007; accepted 24 September 2007

Abstract

Azo dyes have received considerable attention because of their association with various human health problems. The aim of the investigation is to determine the adsorption behavior of azo dyes in aqueous solution on DG06, GSE17200, and GSE17201 soils using C. I. Acid Red 14 (AR14) as example. The experimental results indicate that the Freundlich model expresses the adsorption isotherm better than the Langmuir model and the pseudo-second-order model achieves adsorption of AR14 on the three soils well. Based on the pseudo-second-order model, the adsorption thermodynamic of AR14 on DG06 soil have been studied and the thermodynamics parameter of ΔG^0 is determined and ΔG^0 value shows the adsorption process of AR14 on DG06 is mainly physical in nature. Furthermore, the effects of temperature, pH and salinity (NaCl) on adsorption have been investigated. The decrease in pH or the increase in salinity enhances the adsorption of AR14 by DG06, GSE17200, and GSE17201.

Key words: soil; azo dyes; C. I. Acid Red 14 (AR14); adsorption isotherm; adsorption kinetics; adsorption thermodynamics

Introduction

Azo dyes are widely used in many industrial fields, such as textile, leather, paper, plastics, rubber, etc. They have been considered as an extremely important pollutant in environment due to their complex composition, high toxicity, poor degradability and great solubility in water (Ramakrishna *et al.*, 1997; Vandevivere *et al.*, 1998; Robinson *et al.*, 2002). At present, owing to wide usage of azo dyes in China, the water and soil have been contaminated widely (Liu *et al.*, 2001; Zhou, 2001).

It is well-recognized that organic pollutants adsorption process can affect their other environmental behaviors such as transport, degradation, volatilization, bioaccumulation, consequently, influence the final fate of these pollutants in environment (Gao *et al.*, 1998). Much research has been done on the adsorption behaviors of azo dyes in aqueous solution by adsorbents such as activated carbon, activated sludge, chitosan and resin (El-Geundi, 1991; Yoshida *et al.*, 1993; Al-Degs *et al.*, 2000; Aksu, 2001; Yu *et al.*, 2004). These studies on adsorption behaviors contribute to the treatment of dye-contaminated wastewater (Robinson *et al.*, 2001). However, reports on the adsorption behaviors of azo dyes in aqueous solution by soils are very few (Ketelsen and Meyer-Windel, 1999). Since the average concentration of total organic dyes in surface soils adjacent

* Corresponding author. E-mail: hjyjs@dlut.edu.cn.

to printing, dyeing or synthetic dying enterprises, has been up to 12.3–3114.0 mg/kg (dry weight) in China (Zhou, 2001), it's very necessary to develop a knowledge base of azo dye's adsorption behaviors on surface soil to evaluate the extents to which soils are contaminated by them and the environmental conditions which affect the adsorption amount by soils.

The objective of this investigation is to determine the adsorption behavior of azo dye in aqueous solution on three kinds of surface soils using C. I. Acid Red 14 (AR14) as sample. Two kinetic models, pseudo-first-order equation and pseudo-second-order equation were used to describe the sorption mechanism of AR14 on the three soils (Lagergren and Svenska, 1898; Ho and McKay, 1999a, 1999b). The Langmuir isotherm and the Freundlich isotherm of AR14 on the three soils were determined respectively. Based on the pseudo-second-order equation, the thermodynamics parameter, ΔG^0 of AR14 on DG06 soil was studied and the adsorption process of AR14 on DG06 has been pointed out. In addition, the effects of pH and salinity (NaCl) on adsorption have been also investigated.

1 Materials and methods

1.1 Materials

The azo dye, C.I. Acid Red 14 (Color Index NO.14720), was obtained from Tianjin Shengda Chemical Factory

(China) and the purity was above 97%. The molecular weight of AR14 was 502.42 and the structure of AR14 is shown in Fig.1.

$$NaO_3S$$
 $N=N$
 SO_3Na

Fig. 1 Chemical structure of C. I. Acid Red 14.

Selected soils GSE17200 and GSE17201 soils were obtained from Bayer Landwirtschaftszentrum, Monheim, Germany. DG06 soil was sampled in the surface layers (0– 20 cm) located in Dalian, Liaoning Province, China. Three kinds of soils were air-dried, sieved to 2 mm and stored in dark at a room temperature ($20 \pm 1^{\circ}$ C). The physical and chemical properties of the three soils are shown in Table 1.

1.2 Adsorption isotherm and kinetics studies

Adsorption isotherm and kinetics studies on DG06, GSE17201 and GSE17200 soils were performed in batch experiments. An exactly known amount of the adsorbent (10 g soil) was weighed into a 250-ml glass stoppered conical flask. Different concentrations of 100 ml AR14 solutions (from 100 to 800 mg/L at six different concentrations) were added to the flasks with the soil. The flasks were then shaken (200 r/min) for 48 h for equilibration at 20±0.5°C. Samples were withdrawn periodically for AR14 concentration analysis. Before analysis samples were separated by centrifugation (10000 r/min, 15 min). After membrane filtration (cellulose acetate, 0.22 µm), the filtrate was analyzed using HPLC. All determinations were performed against a soil blank to correct for possible interferences in the measurement of the dye. All samples were in triplicate.

1.3 Adsorption thermodynamics studies

DG06 soil was selected for study of adsorption thermodynamics. Each conical flask was supplemented with 100 ml AR14 solution (300 mg/L). These conical flasks were placed on a rotary shaker (200 r/min) at different temperature $(10 \pm 0.5^{\circ}\text{C}, 20 \pm 0.5^{\circ}\text{C}, 30 \pm 0.5^{\circ}\text{C})$. Samples were withdrawn periodically for AR14 concentration analysis. The adsorption kinetics at different temperatures (10 \pm 0.5° C, $20 \pm 0.5^{\circ}$ C, $30 \pm 0.5^{\circ}$ C) was studied especially.

1.4 Effects of pH and salinity on the adsorption isotherm

To test the effect of pH on the adsorption isotherms of the three soils, each conical flask was supplemented with 100 ml AR14 solution (300 mg/L). The pH value of AR14 solution varied from 2.0 to 10.0. The pH of each solution was adjusted to the required value with diluted or concentrated HCl and NaOH solutions before mixing the soils. These conical flasks were placed on a rotary shaker (200 r/min) at 20 ± 0.5 °C. At the equilibrium time, samples were withdrawn for AR14 concentration analysis. The effect of initial pH (from 2.0 to 10.0) of AR14 solution (300 mg/L) on pH of the systems (AR14 solution + soil) was determined. The same setup was also used for testing the effect of salinity (specially, NaCl) on the adsorption isotherms of the three soils. The quality concentration of NaCl in AR14 solution were 0.2%, 0.5%, 1%, 2%, and 4%.

1.5 Analytical methods

The concentration of AR14 in aqueous solution was monitored with HPLC (1100-FLD, Agilent Technologies, USA). The column is Waters Bondpak C18 (4.6 mm \times 250 mm). The mobile phase was methanol/water (40:60, V/V) and the flow rate was 1 ml/min. The detector wavelength was set at 516 nm.

The amounts of AR14 adsorbed by the three soils, q_e (mg/g), were calculated by the following equation:

$$q_{\rm e} = \frac{(C_0 - C_{\rm e}) \times V}{M} \tag{1}$$

where, C_0 and C_e are the initial and equilibrium concentrations of AR14 in solution (mg/L), respectively. V is the total volume of the AR14 solution (L), and M is the mass of soils used (g).

2 Results and discussion

2.1 Effect of initial dye concentration on AR14 adsorption

Initial concentration has an important effect on adsorption, which can give a driving force to overcome all mass transfer resistances of the dye between the liquid and solid phases. Hence a higher initial concentration of dye will enhance the sorption process. In this study, the effect of initial dye concentration on the dye adsorption capacity was investigated between 100 and 800 mg/L at 20 ± 0.5 °C, the results are presented in Table 2. As listed in Table 2, when initial dye concentration is 100 mg/L, the dye uptake efficiencies of AR14 on DG06, GSE17200, and GSE17201 soils are high, and they are 21.9%, 10.4%, and 8.0%, respectively. With the increase in initial concentration, although the equilibrium adsorption amount (q_e) significantly increases, the dye uptake efficiency takes on a decrease trend. When the initial dye concentration reaches 800 mg/L, the dye uptake efficiency has the lowest values

Table 1 Physical and chemical properties of the tested soils

Soil	pH (0.01 mol/L)	OC (%)	CEC (cmol/kg)	Clay (%)	Silt (%)	Sand (%)
DG06	7.0	3.62	18.5	26.40	34.95	38.65
GSE17200	7.3	0.86	8	12.00	51.10	36.90
GSE17201	6.3	2.48	10	7.20	12.30	80.50
OC: organic carb	oon; CEC: cation exchange ca	apacity.				
					٠ <u>, ((</u>	(5)

Table 2 Equilibrium adsorption amounts (q_e) and the uptake efficiency (R) of AR14 obtained at different initial dye concentrations (C_0) at $20\pm0.5^{\circ}$ C

C_0 (mg/L)	DG06		GSE17	200	GSE17201		
	q _e (mg/g)	R (%)	q _e (mg/g)	R (%)	q _e (mg/g)	R (%)	
100	0.22	21.9	0.10	10.4	0.07	8.0	
200	0.34	16.9	0.20	9.8	0.15	7.3	
300	0.43	14.3	0.31	10.1	0.26	7.5	
400	0.57	14.2	0.41	10.1	0.30	7.5	
600	0.77	12.8	0.46	7.7	0.35	5.9	
800	0.82	10.2	0.49	6.1	0.37	4.5	

that are 10.2%, 6.1%, and 4.5% for DG06, GSE17200, and GSE17201, respectively. This may result from the saturation of the sorption sites on the soils as the dye concentration increases.

2.2 Adsorption isotherm

The Langmuir model equation is (Benefield *et al.*, 1982; Mall *et al.*, 2005):

$$\frac{C_{\rm e}}{q_{\rm e}} = \frac{1}{K_{\rm L}Q_0} + \frac{C_{\rm e}}{Q_0} \tag{2}$$

where, q_e (mg/g) is the amount of dye adsorbed at the point of equilibrium, C_e (mg/L) is the equilibrium dye concentration in solution, Q_0 (mg/g) is the monolayer saturation capacity of the adsorbent, and K_L (L/mg) is the Langmuir adsorption constant. A plot of C_e/q_e vs C_e gives a straight sloping line $1/Q_0$ and intercept $1/K_LQ_0$.

The Freundlich equation is (Adamson, 1990):

$$\log q_{\rm e} = \log K_{\rm F} + \left(\frac{1}{n}\right) \times \log C_{\rm e} \tag{3}$$

where, $q_{\rm e}$ (mg/g) is the amount of dye adsorbed at the point of equilibrium, $C_{\rm e}$ (mg/L) is the equilibrium dye concentration in solution, and $K_{\rm F}$ (L/mg) and n are Freundlich constants which can be calculated from the logarithmic plot of $q_{\rm e}$ vs $C_{\rm e}$.

Table 3 shows the values of Q_0 , K_L , K_F , 1/n and the correlation coefficients for Langmuir (R_L^2) and for Freundlich (R_F^2). In Table 3, the values of R_F^2 for soils of DG06, GSE17200, and GSE17201 are 0.9869, 0.9448, and 0.9216 respectively, which are higher than the corresponding R_L^2 values (0.9392, 0.8561, and 0.7151). The experimental data of the adsorption isotherm are correlated by the Freundlich equation better than by the Langmuir equation. So the Freundlich equation expresses the adsorption isotherms of AR14 on the three soils better than the Langmuir equation over the entire range of concentrations.

Figure 2 shows the adsorption isotherm of of AR14 adsorbed by DG06, GSE17200, and GSE17201 soils. Based on the Freundlich equation, when $C_e = 1$, the value of K_F coincides with the adsorbed concentration (q_e) , and hence




Fig. 2 Equilibrium isotherm of AR14 adsorbed by DG06, GSE17200 and GSE17201 soils. Inserts show the linearized Freundlich isotherms used for the fitting.

can be used to compare the relative adsorption capacity on different adsorbents. So the relative soil adsorption capacity of AR14 on the three soils could be obtained through the comparison of their corresponding K_F values. As shown in Table 3, the K_F values of AR14 on DG06, GSE17200, and GSE17201 soils are 7.1×10^{-3} , 4.8×10^{-3} , and 3.2×10^{-3} respectively. These results indicate DG06 has the highest adsorption capacity among the three soils. In addition, according to the classification of Giles et al. (1960) adsorption isotherms of the AR14 on the three soils follow L-type (n > 1) curves, which indicate that the adsorption firstly occurs on the high energy sites of adsorbents, follows by the low energy sites (Alok and Xu, 2001). Furthermore, the adsorption affinity of the dye appears to be positively correlated with the clay content of the soils and adsorption increases in the following order: GSE17201 (7.20% clay), GSE17200 (12.00% clay), and DG06 (26.40% clay). This finding is agreement with Ketelsen and Meyer-Windel (1999) who reported a strong positive correlation between Brilliant Blue FCF (dye tracer) and clay contents of soils.

2.3 Adsorption kinetics

To study the process of AR14 adsorption by the surface soil, two kinetic models, pseudo-first order equation and pseudo-second order equation are used to describe the mechanism of adsorption.

 Table 3
 Adsorption isotherm data described the adsorption of AR14 by the three soils

Soil	Langmuir isotherm			I	Freundlich isotherm	m	
	Q_0	$K_{ m L}$	$R_{\rm L}^2$	K_{F}	1/n	R_{F}^{2}	
DG06	1.38	2.1×10 ⁻³	0.9392	7.1×10 ⁻³	0.6262	0.9869	
GSE17200	0.98	1.5×10^{-3}	0.8561	4.8×10^{-3}	0.7567	0.9448	
GSE17201	0.83	1.2×10^{-3}	0.7151	3.2×10^{-3}	0.8081	0.9216	

The expression of the pseudo-first-order model is:

$$\log(q_1 - q_t) = \log(q_1) - \frac{K_1}{2.0303}t\tag{4}$$

where, q_1 (mg/g) is the amount of dye adsorbed at the point of equilibrium, q_t (mg/g) is the amount of dye adsorbed at time t, and K_1 (min⁻¹) is the rate constant which can be calculated from the straight-line plot of $\log(q_1-q_t)$ vs t.

The pseudo-second-order model equation is:

$$\frac{t}{q_t} = \frac{1}{K_2 q_2^2} + \frac{1}{q_2} t \tag{5}$$

where, q_2 (mg/g) is the amount of dye adsorbed at the equilibrium time, q_t (mg/g) is the amount of dye adsorbed at time t, and K_2 (min⁻¹) is the rate constant which can be calculated from the straight-line plot of t/q_t vs t.

Figure 3 shows the adsorption kinetics of AR14 by the three soils at 300 mg/L initial dye concentration. The adsorption kinetic parameters of the two models determined are shown in Table 4. The correlation coefficients (R^2) of the pseudo-first-order model for DG06, GSE17200, and GSE17201 soils are 0.9370, 0.9246, and 0.9186, respectively. The correlation coefficients (R^2) of the pseudo-second-order model are 0.9991, 0.9904, and 0.9946, respectively (insert in Fig.3). So the pseudosecond-order model is more significant than the pseudofirst-order model. In addition, the calculated q_1 values from the pseudo-first-order model do not give reasonable values, which are too low compared to experimental q_e values. However, the calculated q_2 values from the pseudo-second-order model are basically same as the experimental q_e values. Therefore, these results demonstrate that the pseudo-second-order kinetic model describes the




Fig. 3 Variation of AR14 adsorption kinetics with DG06, GSE17200, and GSE17201 soils; the insert figure shows the Pseudo-second-order sorption kinetics used for the fitting. Initial dye concentration: 300 mg/L, $20 \pm 0.5^{\circ}$ C, significance at P < 0.05.

adsorption process of AR14 by the three soils better than pseudo-first-order model. Furthermore, based on the pseudo-second-order model, the initial adsorption rates (mg/(g·min)) of AR14 on the three soils are calculated by the following equation (Ho and McKay, 1999b) $v = K_2q_2^2$, which are also listed in Table 4. Comparing these determined kinetic parameters shown in Table 4, AR14 on DG06 soil has the highest rate constant ($K_2 = 0.078$) and the initial adsorption rate (v = 0.0130) among the three soils. Therefore, AR14 is more quickly adsorbed by DG06 soil than by the other two soils.

2.4 Adsorption thermodynamics

As described above, DG06 soil has higher adsorption capacity and can more quickly adsorb AR14 than GSE17200 and GSE17201 soils, so DG06 soil was used to further study adsorption thermodynamics of AR14, based on the pseudo-second-order model. Fig.4 shows at different temperatures the variation of AR14 adsorption kinetics with DG06 soil.

The adsorption kinetic parameters of AR14 by DG06 at 10, 20, and 30°C are measured and shown in Table 5. The correlation coefficients at three different temperatures are higher than 0.99, which means the adsorption process can be expressed well by the pseudo-second-order adsorption equation at the temperature range from 10 to 30°C. According to these kinetic parameters determined, the thermodynamic parameters of standard free energy (ΔG^0) , enthalpy (ΔH^0) , and entropy (ΔS^0) are measured by using the following equations (Catena and Bright, 1989; Namasivayam and Yamuna, 1995):

$$K_{\rm C} = \frac{q_{\rm e}}{C_{\rm e}} \tag{6}$$

$$\Delta G^0 = -RT \ln K_{\rm C} \tag{7}$$

$$\log K_{\rm C} = \frac{\Delta S^0}{2.303R} - \frac{\Delta H^0}{2.303RT} \tag{8}$$




Fig. 4 Effect of temperature on the adsorption kinetics of AR14 on DG06 soil. Initial dye concentration: 300 mg/L, significance at P < 0.05.

 Table 4
 Kinetics parameters described the adsorption of AR14 by the three soils

Soil]	Pseudo-first-order			Pseudo-second-order			
	K_1	q_1	R^2	K_2	q_2	ν	R^2	
DG06	0.0020	0.126	0.9370	0.078	0.410	0.0130	0.9991	0.407
GSE17200	0.0010	0.152	0.9246	0.035	0.306	0.0033	0.9904	0.307
GSE17201	0.0014	0.166	0.9186	0.038	0.281	0.0030	0.9946	0.278

where, $K_{\rm C}$ is the equilibrium constant, $q_{\rm e}$ is the amount of dye (mg) adsorbed on the adsorbent medium per dm³ of the solution at equilibrium, and $C_{\rm e}$ (mg/dm³) is the equilibrium concentration of the dye in the solution. T (K) is the solution temperature and R is the gas constant.

It is well known that the absolute magnitude of the change in free energy for physisorption is between -20 and 0 kJ/mol; chemisorption has a range of -80 to -400 kJ/mol (Jaycock and Parfitt, 1981). As shown in Table 5, the values of ΔG^0 at 10, 20, and 30°C are -1.52, -1.66, and -1.76 kJ/mol respectively. Based on the values of ΔG^0 , it can be concluded that the adsorption process of AR14 by DG06 is mainly physical in nature. The positive value of the standard enthalpy change (ΔH^0), of 1.88 kJ/mol, indicates that the interaction of AR14 with DG06 is an endothermic reaction.

2.5 Effect of pH

Figure 5 shows the effect of initial solution pH on the adsorption of AR14 by DG06, GSE17200, and GSE17201 at $20 \pm 0.5^{\circ}$ C. The initial concentration of AR14 is 300 mg/L. When the values of pH range from 10.0 to 4.0, the amount of adsorption at the point of equilibrium increases slightly, whereas with pH from 4.0 to 2.0, the amount increases significantly. As we know there are generally components with variable charges (e.g., Fe/Mn oxides, organic matter, and kaolinite) in natural soils (Rao and He, 2006) and hydroxyl groups existing on the surfaces soils. Nevskaia *et al.* (1998) have described some surface processes as follows:

$$\equiv S - OH + OH^- \longleftrightarrow \equiv S - O^- + H_2O \tag{9}$$

$$\equiv S - NH_4^+ + OH^- \longleftrightarrow \equiv S - NH_3 + H_2O \tag{10}$$

where, \equiv S is a surface site on soil particles.




Fig. 5 Effect of initial solution pH on the adsorption of AR14 by DG06, GSE17200 and GSE17201 as well as on pH of the systems (AR14 solution + soil). Initial dye concentration: 300 mg/L, $20 \pm 0.5^{\circ}\text{C}$.

According to the above formula, positive charges and hydroxyl groups will increase with the decrease in pH. So the decrease of pH in solutions increases the electrostatic bonding between the soils and AR14; consequently, increases the adsorption of AR14 on the three soils. When the initial AR14 solution pH ranges from 10.0 to 4.0, due to pH buffer capacity of the soils, the pH of the systems (AR14 solution + soil) decreased slightly. However, when the initial AR14 solution pH is lower than 4.0, since the pH buffer capacity of the soils are damaged, pH of the systems decreases significantly, and the adsorption of AR14 on the three soils increases significantly. These results suggest that an acidic condition is helpful in adsorption of AR14 on these three soils.

2.6 Effect of salinity

Industrial dyeing-wastewater usually has high inorganic salt level (specially, NaCl) (Low and Lee, 1997). It is necessary to investigate the adsorption of AR14 by DG06, GSE17200, and GSE17201 soils in the presence of NaCl. Fig.6 shows the effect of salinity (NaCl) on the adsorption of AR14 by the three soils. The concentration of NaCl ranges from 0.2% to 4%. As shown in Fig.6, the amount of equilibrium adsorption increases with the increase in salinity. Generally, there are negative charges in surface soil. Under higher NaCl concentrations, more Na⁺ can react with negative charges, which results in the reduction of electrostatic repulsion between RSO₃⁻ anion and negatively charged surface soils. Thus, the amount of AR14 adsorbed by the three soils will increase with the increase in salinity.




Fig. 6 Effect of salinity (NaCl) on the adsorption of AR14 by DG06, GSE17200 and GSE17201. Initial dye concentration: 300 mg/L, $20\pm0.5^{\circ}$ C, significance at P < 0.05.

 Table 5
 Kinetic and thermodynamic parameters of AR14 determined on DG06 soil

Temp. (°C)	Kinetic parameters of the pseudo-second-order			Thermodynamic parameters					
	K_2	q_2	v	R^2	K _C	ΔG^0 (kJ/mol)	ΔH^0 (kJ/mol)	ΔS^0 (J/molK)	R^2
10	0.049	0.398	7.82×10^{-3}	0.9978	1.91	-1.52			
20	0.078	0.410	1.30×10^{-2}	0.9991	1.98	-1.66	1.88	12.05	0.9984
30	0.220	0.416	3.82×10^{-2}	0.9998	2.01	-1.76			C10

3 Conclusions

This paper reports on the adsorption of azo dye AR14 by DG06, GSE17200, and GSE17201 soils. Adsorption isotherm, adsorption kinetic and adsorption thermodynamics were systematically studied for AR14 on the three soils. The adsorption isotherm indicates that the Freundlich model expresses the adsorption behavior better than the Langmuir model. Among the three soils, DG06 has the highest $K_{\rm F}$. The pseudo-second-order model expresses the adsorption kinetics well. DG06 has the higher values of q_e , K_2 , and v than the other two soils. These results demonstrate that compared to GSE17200 and GSE17201, DG06 has the higher initial adsorption rate and higher adsorption capacity, which is easier to be polluted by AR14. The thermodynamic parameter of ΔG^0 suggests that the adsorption process of AR14 by DG06 is mainly physical in nature. In addition, the effect of pH and salinity (NaCl) on the adsorption was also investigated and the results showed that pH and salinity can influence the amount of adsorption at the point of equilibrium. The decrease of pH or the increase of salinity can enhance the adsorption of AR14, thus increase the extent to which the three soils are polluted by AR14.

Acknowledgements

This work was supported by the Scientific Research Foundation for the Returned Overseas Chinese Scholars, State Education Ministry (No. 2002247). We thank associated-professor Aili Zhang in Dalian University of Technology for helpful discussions.

References

- Adamson A W, 1990. Physical Chemistry of Surfaces (5th ed.). New York: John Wiley and Sons, Inc.
- Aksu Z, 2001. Biosorption of reactive dyes by dried activated sludge: equilibrium and kinetic modeling. *Biochem Eng J*, 7: 79–84.
- Al-Degs Y, Khraisheh M A M Allen S J, Ahmad M N, 2000. Effect of carbon surface chemistry on the removal of reactive dyes from textile effluent. *Water Res*, 34: 927–935.
- Alok B, Xu F X, 2001. Impact of peroxidase addition on the adsorption-deadsorption behavior of phenolic contaminants in surface soils. *Environ Sci Technol*, 35: 3163–3168.
- Benefield L D, Judkins J F, Weand B L, 1982. Process Chemistry for Water and Wastewater Treatment. New Jersey: Prentice-Hall, Inc.
- Catena G C, Bright F V, 1989. Thermodynamic study on the effects of β-cyclodextrin inclusion with anilinonaphthalene-sulfonates. *Anal Chem*, 61: 905–909.
- El-Geundi M S, 1991. Color removal from textile effluents by adsorption techniques. *Water Res*, 25: 271–273.
- Gao J P, Maguhn J, Spitzauer P, Spitzauer P, Kettrup A, 1998. Sorption of pesticides in the sediment of the Teufelesweiher pond (southern Germany). I: equilibrium assessments,

- effect of organic carbon content and pH. *Water Res*, 32(5): 1662–1672.
- Giles C H, MacEwen T H, Nakhwa S N, Smith D, 1960. Studies in adsorption. Part II. A system of classification of solution adsorption isotherms, and its use in diagnosis of adsorption mechanisms and in measurement of specific surface areas of solids. *J Chem Soc*, 3973–3993.
- Ho Y S, McKay G, 1999a. The sorption of lead(II) ions on peat. *Water Res*, 33: 578–584.
- Ho Y S, McKay G, 1999b. Pseudo-second order model for sorption processes. *Process Biochem*, 34(5): 451–465.
- Jaycock M J, Parfitt G D, 1981. Chemistry of Interfaces. New York: John Wiley and Sons, Inc.
- Ketelsen H, Meyer-Windel S, 1999. Adsorption of Brilliant Blue FCF by soils. *Geoderma*, 90: 131–145.
- Lagergren S, Svenska B K, 1898. Zur theorie der sogenannten adsorption gelöster. Veternskapsakad Handlingar, 24: 1–39.
- Liu R X, Liu X M, Tang H G, Su Y, 2001. Sorption behavior of dye compounds onto natural sediment of Qinghe River. J Colloid Interface Sci, 239: 475–482.
- Low K S, Lee C K, 1997. Quaternized rice husk as sorbent for reactive dyes. J Bioresource Technol, 61: 121–125.
- Mall I D, Srivastava V C, Agarwal N K, Mishra I M, 2005. Removal of Congo Red from aqueous solution by bagasse fly ash and activated carbon: kinetic study and equilibrium isotherm analyses. *Chemosphere*, 61: 492–501.
- Namasivayam C, Yamuna R T, 1995. Adsorption of Direct Red 12B by biogas residual slurry: equilibrium and rate processes. *Environ Pollut*, 89: 1–7.
- Nevskaia D M, Guerrero-Ruíz A, de D López-González J, 1998. Adsorption of polyoxyethylenic nonionic and anionic surfactants from aqueous solution: Effects induced by the addition of NaCl and CaCl₂. J Colloid Interface Sci, 205: 97–105.
- Ramakrishna K R, Viraraghavan T, Andreadakis A, 1997. Dye removal using low cost adsorbents. Water Sci Technol, 36: 189–196.
- Rao P H, He M, 2006. Adsorption of anionic and nonionic surfactant mixtures from synthetic detergents on soils. *Chemosphere*, 63: 1214–1221.
- Robinson T, Mcmullan G, Marchant R, Nigam P, 2001. Remediation of dyes in textile effluent: a critical review on current treatment technologies with a proposed alternative. *Biores Technol*. 77: 247–255.
- Robinson T, Chandran B, Nigam P, 2002. Removal of dyes from a synthetic textile dye effluent by biosorption on apple pomace and wheat straw. *Water Res*, 36: 2824–2830.
- Vandevivere P C, Bianchi R, Verstraete W, 1998. Treatment and reuse of wastewater from the textile wet-processing industry: review of emerging technologies. *J Chem Technol Biotechnol*, 72: 289–302.
- Yoshida H, Okamoto A, Kataoka T, 1993. Adsorption of acid dye on cross-linked chitosan fibers: equilibria. *Chem Eng Sci*, 48: 2267–2272.
- Yu Y, Zhuang Y Y, Wang Z H, Qiu M Q, 2004. Adsorption of water-soluble dyes onto modified resin. *Chemosphere*, 54: 425–430.
- Zhou Q X, 2001. Chemical pollution and transport of organic dyes in water-soil-crop systems of the Chinese coast. *Bull Environ Cont Toxicol*, 66(6): 784–793.